

VIDEOTECH SERVICE CENTRE




Professional Security & Surveillance Systems (since 1986)
Asma Manzil, 2nd Floor, New Nagpada Police Stn. Lane, Mumbai – 400 008

Email: videotechservicecentre@hotmail.com
malpekar@hotmail.com

Website : <http://videotech.co.in>

Tel:- 23071753

Cell:-9820150122

	 10x	 10x	 30x
Model No	<u>UMSD-710</u>	<u>UMSD-710(W)</u> Waterproof	<u>UMSD-730(W)</u> Waterproof
Image Sensor	1/3 " Sony CCD		
Signal Model	PAL / NTSC		
Efficient Pixel	976 (H) x 596(V)		
H-Resolution	700 TVL		
Lens	F=3.9 – 39mm		F=3.2 – 86.4mm
Optical Zoom	10x		30x
Min. Illumination	0.01 Lux (Color); 0.001 Lux (Black / White)		0 Lux (IR on)
Shutter Time	Pal : 1/50-1/10000s; NTSC: 1/60-1/12000S		
S/N Ratio	>60dB		>50dB
IR Lighting Distance	40m	50m	120m
Day & Night			IR Cut Filters
IR Control			Auto
IR Model			Auto / Manual / Timing / Synch
Pan	360° Continuous		
Tilt	0° - 90°		10° - 90°
Speed Max.	30° /s	80 /s	200° /s
Manual Control Speed	0.01° – 200° / Second	0.01° – 200° / Second	0.01° – 180° / Second
Protocal	PELCO-D, PELCO-P,RS485		
Tem. Control	Built-In		
Supply Voltage	DC12V (2A)	DC12V (3A)	DC12V (4A)
Material	Aluminum Sheel		
Operating Tem.	-20° C-50° C (Tem. Control System Is Optional), <95%RH		-35° C - 65° C
Gross Weight	2Kg	3Kg	4.3Kg
Assembly Parts	Bracket (Wall Or Ceiling), User manual , Power Supply , Screws		
Package Dimension	185(L) x 185(W) x 240(H)mm	350(L) x 270(W) x 210(H)mm	



SD-87

- 4.5' Mini – PTZ Dome (360°)
- 1/3' Sony Color CCD
- 700 TV Lines
- Pan: 360° Non – Stop ; Tilt : 95°
- Preset Speed : 0.5 ~ 45° / Sec.
- 128 Preset Points ; 2 Auto-Scan
- Sync – Focus Lens : 5-15mm (F2.2, 2.0 MP) , 8-20mm (F1.8, 1.3 MP)
- Communication : Rs485, PELCO ~ D / P Protocol
- Min. Illumination : 0.01 Lux
- Auto ~ Focus During Zooming In/Out
- Memory Function At accidental Power Off
- Super Wide Voltage CCD Board Design : 8-15V



CKSD-100 (Keyboard Controller)